

Standard Wagon Gears



WG1208

Farmco wagon gears are ready for everyday farm abuse! Towing is straight and true with a heavy duty, automotive-type steering mechanism and an adjustable steering rod. Easily mount your gravity bin or bale wagon with the adjustable length reach pole and mounting stakes.

The Model 1208 is an ideal running gear for use under forage boxes and other heavy-duty applications. The tandem walking beam pivot point is 2" off center for reduced stress on tandem axles when turning. Formed steel axle assemblies are rigidly reinforced and gusseted to give the best capacity for the weight. The heavy-wall, round-tubing reach pole resists bending under pressure.

120" reach pole available for 20' or longer applications



Tandem axle models feature a **Walking Beam** that is offset 2" toward the rear axle. Because this throws a little more weight on the rear axle, the front axle enters holes and ditches more smoothly. The offset walking beam creates greater stability and a better ride over uneven ground.



WG88

Model#	Rear Axle	Capacity	Hubs	Spindle Size	Bearing Diameter	Reach Pole	Tread Width	Rims	Recommended Tires	Weight w/o Rims
88	Single	16,000 lbs.	6 Bolt	1 3/4"	1 1/2 & 1 1/4	80" 2 1/2" Sch. 40 Pipe	74"	15x8	11L15	510
98	Single	16,000 lbs.	6 Bolt	1 3/4"	1 1/2 & 1 1/4	80" 2 1/2" Sch. 40 Pipe	88"	15x8	11L15	585
108	Single	20,000 lbs.	8 Bolt	2 1/8"	1 3/4 & 1 3/8	80" 2 1/2" Sch. 80 Pipe	77"	15x10	11L15 or 12.5L15	675
1208	Tandem	24,000 lbs.	8 Bolt	2 1/8"	1 3/4 & 1 3/8	80" 2 1/2" Sch. 80 Pipe	77"	15x10	11L15 or 12.5L15	940